



## 3-Channel Power Unit, 420 W (600 W)

Item No: WXR3N

3-Channel Power Unit, 420 W (600 W)

### KEY FEATURES

- + All-in-one-Station
- + Benchtop controller capability e.g. Zero Smog Systems
- + Automatic tool recognition and power management
- + Compatible with all WX tools
- + Storage medium in hand piece
- + Blue LED backlighting
- + Multilingual menu navigation

## TECHNICAL DATA

Dimensions L x W x H	273.0 x 235.0 x 102.0mm
Automatic Tool Identification	Yes
Benchtop Controller	Yes
Capacity (l/min)	18 l/min
Equipotential Bonding	Yes
Equipotential Bonding Socket	Via 3.5mm Pawl Socket on Back of Device (Hard-Grounded)
ESD Safe	Yes
Fuse	2.0A
Interface	1x USB, 2x RS232, 2x Switching Output
IPC Compliant	Yes
Maximum Hot Air Flow Rate l/min (Depends on Tool)	15 l/min
Maximum Volume	0.7 bar
Multilingual Display	Yes
Number of Channels	3
Power	420 W (600 W)
Temperature Accuracy °C	± 9 °C
Temperature Accuracy °F	±9 °C
Temperature Accuracy for Hot Air	±30 °C
Temperature Range °C	93 - 454 °C (537 °C)
Temperature Range °F	199 - 849 °F (998 °F)
Temperature Stability °C	±2 °C
Temperature Stability °F	±2 °C
Traceability	Yes
UPC	037103304254
USB	USB interface of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types